

L型不锈钢粘塑带

Stainless Steel Cable Ties-L Type PVC Coated Ties

技术信息

- 产品材料：不锈钢材质304或316
- 喷塑材料：PVC电缆料
- 操作温度：-40℃~85℃
- 产品描述：黑色带身及金属色搭扣
- 防火等级：阻燃
- 材料特性：抗紫外线

产品特性

- PVC粘塑挤带，相较于PPA可以节省安装成本；
- 与喷塑带身相比，更厚，更软，更能保护被捆绑物；
- 粘塑带身可以避免金属间的腐蚀。



Technical information

- Material: Stainless Steel Grade 304 or 316
- Coating: PVC
- Working Temp: -40°C to 85°C
- Description: Black Band with Metallic Buckle
- Flammability: Fireproof
- Other Properties: UV-resistant

Product Feature

- PVC coating will reduce the cost, than PPA coating.
- Softer and thicker PVC provide additional edge protection.
- Prevent the corrosion between dissimilar materials.

规格型号 Part Number	宽度 width		长度 Length		厚度 Thickness		最大捆绑直径 Max.Bundle Dia		最小捆绑直径 Min.Bundle Dia		最小拉力 Min.Tensile Strength	
	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	N	lbs
GBL 9×300	9	0.35	300	11.81	1.0	0.039	60	2.36	12.7	0.50	2220	450
GBL 9×400			400	15.75			92	3.62				
GBL 9×500			500	19.69			124	4.88				
GBL 9×600			600	23.62			156	6.14				
GBL 9×700			700	27.56			188	7.40				
GBL 9×800			800	31.50			220	8.66				
GBL 9×900			900	35.43			252	9.90				
GBL 9×1000			1000	39.37			284	11.18				
GBL 9×1100			1100	43.31			313	12.30				
GBL 9×1200			1200	47.24			348	13.70				

规格型号 Part Number	宽度 width		长度 Length		厚度 Thickness		最大捆綁直径 Max.Bundle Dia		最小捆綁直径 Min.Bundle Dia		最小拉力 Min.Tensile Strength	
	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	N	lbs
GBL 11 × 300	11	0.43	300	11.81	1.0	0.039	60	2.36	19.05	0.75	2800	630
GBL 11 × 400			400	15.75			92	3.62				
GBL 11 × 500			500	19.69			124	4.88				
GBL 11 × 600			600	23.62			156	6.14				
GBL 11 × 700			700	27.56			188	7.40				
GBL 11 × 800			800	31.50			220	8.66				
GBL 11 × 900			900	35.43			252	9.90				
GBL 11 × 1000			1000	39.37			284	11.18				
GBL 11 × 1100			1100	43.31			313	12.30				
GBL 11 × 1200			1200	47.24			348	13.70				
GBL 13 × 300	13	0.51	300	11.81	1.2	0.047	60	2.36	25.4	1.0	3000	675
GBL 13 × 400			400	15.75			92	3.62				
GBL 13 × 500			500	19.69			124	4.88				
GBL 13 × 600			600	23.62			156	6.14				
GBL 13 × 700			700	27.56			188	7.40				
GBL 13 × 800			800	31.50			220	8.66				
GBL 13 × 900			900	35.43			252	9.90				
GBL 13 × 1000			1000	39.37			284	11.18				
GBL 13 × 1100			1100	43.31			313	12.30				
GBL 13 × 1200			1200	47.24			348	13.70				
GBL 16 × 300	16	0.63	300	11.81	1.2	0.047	60	2.36	25.4	1.0	3500	790
GBL 16 × 400			400	15.75			92	3.62				
GBL 16 × 500			500	19.69			124	4.88				
GBL 16 × 600			600	23.62			156	6.14				
GBL 16 × 700			700	27.56			188	7.40				
GBL 16 × 800			800	31.50			220	8.66				
GBL 16 × 900			900	35.43			252	9.90				
GBL 16 × 1000			1000	39.37			284	11.18				
GBL 16 × 1100			1100	43.31			313	12.30				
GBL 16 × 1200			1200	47.24			348	13.70				

滚珠自锁式不锈钢光带

Stainless Steel Cable Ties-Ball Lock Uncoated Ties

技术信息

- 产品材料：不锈钢材质304或316
- 操作温度：-80℃~538℃
- 产品描述：金属色带身及搭扣
- 防火等级：阻燃
- 材料特性：抗紫外线

产品特性

- 滚珠式自锁结构有利于加快安装速度

Technical information

- Material: Stainless Steel Grade 304 or 316
- Working Temp: -80℃ to 538℃
- Description: Entirely metallic
- Flammability: Fireproof
- Other Properties: UV-resistant

Product Feature

- Ball-Lock type self-lock system will speed the installation



规格型号 Part Number	宽度 width		长度 Length		厚度 Thickness		最大捆绑直径 Max.Bundle Dia		最小捆绑直径 Min.Bundle Dia		最小拉力 Min.Tensile Strength	
	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	N	lbs
G-C 4.6 × 100	4.6	0.18	100	3.9	0.26	0.010	25	1.00	12.7	0.50	1100	250
G-C 4.6 × 150			150	5.9			37	1.46				
G-C 4.6 × 200			200	7.9			50	1.97				
G-C 4.6 × 250			250	9.8			63	2.50				
G-C 4.6 × 300			300	11.8			76	3.00				
G-C 4.6 × 350			350	13.8			89	3.51				
G-C 4.6 × 400			400	15.7			102	4.00				
G-C 4.6 × 450			450	17.7			115	4.50				
G-C 4.6 × 500			500	19.7			128	5.00				
G-C 4.6 × 550			550	21.7			141	5.56				
G-C 4.6 × 650			650	25.6			167	6.58				
G-C 4.6 × 700			700	27.6			179	7.05				
G-C 4.6 × 800			800	31.5			193	7.60				
G-C 4.6 × 900			900	35.4			200	7.87				
G-C 4.6 × 1000			1000	39.4			206	8.12				
G-C 4.6 × 1100			1100	43.3			278	10.94				

规格型号 Part Number	宽度 width		长度 Length		厚度 Thickness		最大捆綁直径 Max.Bundle Dia		最小捆綁直径 Min.Bundle Dia		最小拉力 Min.Tensile Strength	
	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	N	lbs
G-C 7.9 × 150	7.9	0.31	150	5.9	0.26	0.010	37	1.46	12.7	0.50	1500	340
G-C 7.9 × 200			200	7.9			50	1.97				
G-C 7.9 × 250			250	9.8			63	2.50				
G-C 7.9 × 300			300	11.8			76	3.00				
G-C 7.9 × 350			350	13.8			89	3.50				
G-C 7.9 × 400			400	15.7			102	4.00				
G-C 7.9 × 500			500	19.7			128	5.00				
G-C 7.9 × 600			600	23.6			154	6.07				
G-C 7.9 × 800			800	31.5			193	7.60				
G-C 7.9 × 1000			1000	39.4			206	8.12				
G-C 10 × 300	10	0.39	300	11.8	0.26	0.010	76	3.00	12.7	0.50	2100	480
G-C 10 × 350			350	13.8			89	3.50				
G-C 10 × 400			400	15.7			102	4.00				
G-C 10 × 500			500	19.7			128	5.00				
G-C 10 × 600			600	23.6			154	6.07				
G-C 10 × 800			800	31.5			193	7.60				
G-C 10 × 1000			1000	39.4			206	8.12				
G-C 12 × 350	12	0.47	350	13.8	0.35	0.014	78	3.07	25.4	1.00	3000	675
G-C 12 × 400			400	15.7			102	4.02				
G-C 12 × 500			500	19.7			128	5.04				
G-C 12 × 600			600	23.6			154	6.06				
G-C 12 × 750			750	29.5			188	7.40				
G-C 12 × 900			900	35.4			228	8.98				
G-C 12 × 1100			1100	43.3			278	10.94				
G-C 12.7 × 350	12.7	0.50	350	13.8	0.35	0.014	78	3.07	25.4	1.00	3200	720
G-C 12.7 × 400			400	15.7			102	4.02				
G-C 12.7 × 500			500	19.7			128	5.04				
G-C 12.7 × 600			600	23.6			154	6.06				
G-C 12.7 × 750			750	29.5			188	7.40				
G-C 12.7 × 900			900	35.4			228	8.98				
G-C 12.7 × 1100			1100	43.3			278	10.94				
G-C 15 × 350	15	0.59	350	13.8	0.35	0.014	78	3.07	25.4	1.00	4000	900
G-C 15 × 400			400	15.7			102	4.02				
G-C 15 × 450			450	17.7			108	4.25				
G-C 15 × 600			600	23.6			148	5.83				
G-C 15 × 750			750	29.5			184	7.24				
G-C 15 × 900			900	35.4			220	8.66				
G-C 15 × 1100			1100	43.3			272	10.71				

L型不锈钢喷带

Stainless Steel Cable Ties-L Type Epoxy Coated Ties

技术信息

- ◉ 产品材料：不锈钢材质304或316
- ◉ 喷塑材料：环氧树脂粉末，尼龙11
- ◉ 操作温度：-80℃~150℃
- ◉ 产品描述：黑色带身及金属色搭扣
- ◉ 防火等级：阻燃
- ◉ 材料特性：抗紫外线，无卤无毒

产品特性

- ◉ 喷塑带身可以提供额外的边缘保护，并避免金属间的腐蚀。



Technical information

- ◉ Material: Stainless Steel Grade 304 or 316
- ◉ Coating: Polyester/Epoxy, Nylon 11
- ◉ Working Temp: -80°C to 150°C
- ◉ Description: Black strap with metallis buckle
- ◉ Flammability: Fireproof
- ◉ Other Properties: UV-resistant, Halogen free, non toxic

Product Feature

- ◉ Coated band provide additional edge protection, prevent the corrosion between dissimilar materials.

规格型号 Part Number	宽度 width		长度 Length		厚度 Thickness		最大捆绑直径 Max.Bundle Dia		最小捆绑直径 Min.Bundle Dia		最小拉力 Min.Tensile Strength	
	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	N	lbs
GPL 7.9×200	7.9	0.31	200	7.87	0.35	0.014	55	2.17	12.7	0.50	2220	500
GPL 7.9×300			300	11.81			90	3.54				
GPL 7.9×400			400	15.75			120	4.72				
GPL 7.9×500			500	19.69			150	5.91				
GPL 7.9×600			600	23.62			185	7.28				
GPL 7.9×700			700	27.56			215	8.46				
GPL 7.9×800			800	31.50			250	9.84				
GPL 7.9×900			900	35.43			280	11.02				
GPL 7.9×1000			1000	39.37			310	12.20				
GPL 7.9×1100			1100	43.31			340	13.39				
GPL 7.9×1200			1200	47.24			370	14.57				

规格型号 Part Number	宽度 width		长度 Length		厚度 Thickness		最大捆绑直径 Max.Bundle Dia		最小捆绑直径 Min.Bundle Dia		最小拉力 Min.Tensile Strength	
	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	N	lbs
GPL 10 × 300	10	0.39	300	11.81	0.35	0.014	90	3.54	19.05	0.75	2800	630
GPL 10 × 400			400	15.75			120	4.72				
GPL 10 × 500			500	19.69			150	5.91				
GPL 10 × 600			900	23.62			185	7.28				
GPL 10 × 700			700	27.56			215	8.46				
GPL 10 × 800			800	31.50			250	9.84				
GPL 10 × 900			900	35.43			280	11.02				
GPL 10 × 1000			1000	39.37			310	12.20				
GPL 10 × 1100			1100	43.31			340	13.39				
GPL 10 × 1200			1200	47.24			370	14.57				
GPL 12 × 300	12	0.47	300	11.81	0.45	0.018	90	3.54	25.4	1.0	3115	700
GPL 12 × 400			400	15.75			120	4.72				
GPL 12 × 500			500	19.69			150	5.91				
GPL 12 × 600			600	23.62			185	7.28				
GPL 12 × 700			700	27.56			215	8.46				
GPL 12 × 800			800	31.50			250	9.84				
GPL 12 × 900			900	35.43			280	11.02				
GPL 12 × 1000			1000	39.37			310	12.20				
GPL 12 × 1100			1100	43.31			340	13.39				
GPL 12 × 1200			1200	47.24			370	14.57				
GPL 15 × 300	15	0.59	300	11.81	0.45	0.018	85	3.54	25.4	1.0	4100	920
GPL 15 × 400			400	15.75			120	4.72				
GPL 15 × 500			500	19.69			150	5.91				
GPL 15 × 600			600	23.62			185	7.28				
GPL 15 × 700			700	27.56			215	8.46				
GPL 15 × 800			800	31.50			250	9.84				
GPL 15 × 900			900	35.43			280	11.02				
GPL 15 × 1000			1000	39.37			310	12.20				
GPL 15 × 1100			1100	43.31			340	13.39				
GPL 15 × 1200			1200	47.24			370	14.57				